# PRODUCT SHEET: GAME AUTHENTICATION STANDARD

GAMING STANDARDS

PROTECT REGULATORS AND REDUCES LIABILITY FOR OPERATORS

PS001-2020: COVID-19 OPERATIONAL SAFETY ENHANCEMENTS

WHY: COVID has taught us that we must roll out virtual solutions to replace manual operations.

# REDUCE EMPLOYEE TO SLOT MACHINE TOUCHPOINTS

Regulatory Agents have to periodically verify that the software running within a slot machine is the approved authentic version. In most cases, performing this task requires a Casino employee to open the slot machine for the Agent who then has to use a device or laptop to perform the required verification.

# ABOUT THIS STANDARD

- GAT has been developed to empower Regulators with remote access to authenticate and ensure compliance of EGM software.
- The Game Authentication Terminal standard (GAT) reduces the burden of the logistics, cost, and management of EGM software integrity surveillance and enforcement.
- GAT allows for the ability to perform EGM software authentication checks from a remote location therefore eliminating the current requirement for Regulators to physically be present on a casino floor.
- GAT can be implemented to automatically disable EGMs that are non-compliant and issue notices.
- GAT comes in two flavors that eliminate the need for casino employees and Regulatory Agents to physically be at the slot machine to authenticate software. Those ate Network GAT and G2S GAT.

### HOW TO IMPLEMENT

### OPERATORS WITH G2S

#### CASINOS G2S GAT is used. Network GAT is used. WITH A FLOOR Additionally, G2S allows users to get a full Network GAT uses a small computer **NETWORK** list of the supplier assigned part number server to connect over the network to the of the software and firmware running in a slot machines on the casino floor. slot machine. This will allow the user to determine if the right software and A HOW-TO Guide is available from IGSA firmware is being used. on how to set up the computer properly. CASINOS WITHOUT A For slot machines that have G2S (most A small wireless iGAT device is put inside FLOOR likely to be in addition to SAS) a small each slot machine and connected to the **NETWORK** wireless iGAT+ is put inside each slot GAT port. The iGAT creates a network machine. The iGAT+ creates a network either using WiFi or Cell connectivity. using WiFi or Cell connectivity.

**OPERATORS WITHOUT G2S** 

